


# COMPARISON CHART

## STRIKER - SERIES



STRIKER 4 w/ Dual Beam xdcr



STRIKER Plus 4cv w/ Dual Beam xdcr




STRIKER Vivid 4cv w/ GT20



STRIKER Vivid 5cv w/o xdcr  
STRIKER Vivid 5cv w/ GT20



STRIKER Vivid 7cv w/ GT20



STRIKER Vivid 7sv w/o xdcr  
STRIKER Vivid 7sv w/ GT52



STRIKER Vivid 9sv w/o xdcr  
STRIKER Vivid 9sv w/ GT52

DISPLAY SIZE	3.5"	4.3"	4.3"	5"	7"	7"	9"
DISPLAY TYPE & RESOLUTION	HVGA 320x480 px	QSVGA 272x480 px	QSVGA 272x480 px	WVGA 800x480 px	WVGA 800x480 px	WVGA 800x480 px	WVGA 1280x800 px
TOUCH OR KEYED PANEL	Keyed	Keyed	Keyed	Keyed	Keyed	Keyed	Keyed
PHYSICAL DIMENSIONS	9.2 x 15.1 x 4.3 cm	9.8 x 17.4 x 4.5 cm	9.8 x 17.4 x 4.5 cm	18.8 x 11.6 x 5.4 cm	23.5 x 14.0 x 5.8 cm	23.5 x 14.0 x 5.8 cm	28.2 x 16.5 x 6.0 cm
RECEIVER	5 Hz	5 Hz	5 Hz	5 Hz	5 Hz	5 Hz	5 Hz
VIVID COLOUR PALETTE			•	•	•	•	•
NMEA 0183	•	•	•	•	•	•	•
USER DATA SHARING COMPATIBLE	•	•	•	•	•	•	•
WIFI® CONNECTIVITY				•	•	•	•
BUILT-IN QUICKDRAW	•	•	•	•	•	•	•
BUILT-IN FLASHER	•	•	•	•	•	•	•
BLUECHART® g3 & g3 Vision COMPATIBLE							
DUAL FREQUENCY (50/200 kHz)	•	•	•	•	•	•	•
DUAL BEAM (77/200 kHz)	•	•	•	•	•	•	•
CHIRP	•	•	•	•	•	•	•
CLEARVÜ		•	•	•	•	•	•
SIDEVÜ						•	•
FREQUENCIES SUPPORTED (kHz)	Traditional: 50/77/200 CHIRP (Low, Mid, High)	CHIRP 77/200 kHz ClearVu (455/800 kHz)	CHIRP 77/200 kHz ClearVü (455/800 kHz)	CHIRP (77/200 kHz) ClearVü (455/800 kHz)	CHIRP (77/200 kHz) ClearVü (455/800 kHz)	CHIRP (77/200 kHz) ClearVü/SideVü (455/800 kHz)	High-Wide CHIRP (150-240 kHz) ClearVü/SideVü (455/800 kHz)
TRANSMIT POWER (INK TRANSDUCER)	200 W Trad	300 W Trad 300 W ClearVü	300 W Trad 300 W ClearVü	500 W Trad 500 W ClearVü	500 W Trad 500 W ClearVü	500 W Trad 500 W ClearVü	250 W Trad 350 W ClearVü/SideVü
PANOPTIX™ SUPPORT							